

# Package 5 LT M0301

#### Volume

Volume under lid: 5 LT Volume brimfull: 5,5 LT  $\pm$  1%

#### **Dimensions**

Shape:	Conical	
External diameter top:	200 mm	±1 mm
Internal diameter top:	185 mm	± 1 mm
External diameter bottom:	164 mm	± 1 mm
Height without lid:	246 mm	± 1 mm
Height with lid:	248 mm	± 1 mm

## Weight - PP

Bucket without handle and without lid:	204 g	± 1,5 g
Bucket with metallic handle and without lid:	223,5 g	± 1,5 g
Bucket with metallic handle and with lid:	265,5 g	± 3,5 g

#### Weight - PCR Black

Bucket without handle and without lid:	209 g	±7 g
Bucket with metallic handle and without lid:	228,5 g	±7g
Bucket with metallic handle and with lid:	270,5 g	±9 g

# Weight - PCR Grey

Bucket without handle and without lid:	220 g	± 7 g
Bucket with metallic handle and without lid:	239,5 g	±7g
Bucket with metallic handle and with lid:	281,5 g	±9 g

# Weight - PIR



# Performance

Stackability - dynamic: Max: 34 Kg \* Maximum topload on bottom container

Stacking Tests:

Our stacking tests are performed on equipment certified for this purpose, and measures the product's resistance to stacking. These stacking tests have been performed under optimal lab conditions, with a standard raw material, as indicated below, and at a stable ambient temperature of 24 °C, confirming the resistance of the package to a maximum static load of 61 kg, distributed evenly and over a 2 months period. The performance, when stacking, of plastic packaging depends on several factors, for example the increase in the ambient temperature can seriously compromise the behavior of the packaging. This technical sheet should be understood as an indicative reference, and customers should carry out their own tests to determine the feasibility of stacking and transport, in the context of their particular conditions.

Exposure to hight temperatures and particularly to direct UV radiation can have a undesirable impact over the Mechanical Properties (MP) and Visual Appearance (VA) of all plastic packaging, namely:

UV Resistance:

- Impact over Mechanical Properties such as: development of molecular weaknesses; decreased strength, loos of elasticity and hardness; formation of stress ruptures.
- Impact over Visual Appearance: yellowing of packaging; degradation of the decoration quality.

Therefore, we do not recommend exposing the plastic packaging to direct sunlight, for prolonged periods of time.

Standard pallet (1200x1000)

Stack quantity: 28 Pieces per pallet: 840

Pallet height: 1250 mm (±5)

Alternative: Europallet (1200x800)

Stack quantity: 28 Pieces per pallet: 672

Pallet height: 1250 mm (±5)

## Decoration

Digital IML: Yes

Visible Area - 554 x 210 mm

Conventional IML: Yes

Visible Area - 554,32 x 209,25 mm

Offset: Yes

Visible Area - 555 x 185 mm

Hot Filling: 85-95°C

#### **Raw Material**

Material: PP Copolymer, Food approved and Composit with PCR

#### Hot temperatures:

The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging becomes flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. This packaging must be tested by costumer with the actual product before approval for use at hot temperatures.

## Cold temperatures:

Freezing conditions require special resins available on request. This packaging must be tested by the costumer with the actual product before use at low temperatures.

#### **Legal Requirements**

Regulation (EC) No. 596/2009, of 18 June and Regulation (EU) 2019/1381 of 20 June, which amendments the Regulation (EC) No. 1935/2004, of 27 October, that generally establishes the rules for the manufacture and marketing of materials and objects intended to come into contact with foodstuffs, including compliance with traceability.

Commission Regulation (EU) 2022/1616 of 15 September 2022 on recycled plastic materials and articles intended to come into contact with food and repealing Regulation (EC) No 282/2008 (Text with EEA relevance).

Regulation (EU) No. 2020/1245 of 2 September, which amendments and rectify the Regulation (EU) No. 10/2011 of 14 January, on plastic materials and objects intended to come into contact with food.

Regulation (EU) No. 10/2011 of 14 January, wich amendments the Directive 85/572 (EEC), that fixes a list of simulators used to verify the migration of constituents of plastic materials and objects intended to come into contact with food.

### **Environment**



We constantly try to ensure that our production process is as sustainable as possible. Production waste is completely recycled in line with efficiency of resources. One important contribution to climate protection is the replacement of virgin materials (raw materials sourced from fossil resources) with recyclate. This cuts down on greenhouse gas emissions. The potential saving can be as much as 2.2 kilograms of CO2 per kilogram of recyclate that replaces virgin materials.

# **Quality Specifications**

Approvals:

MGR Packaging, SA products comply with the European Union Commission Regulation No. 10/2011/EC with ammendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the costumer to ensure that the supplied product is suitable for the intended use.

Shelf life:

The adherence of the product to the aforementioned technical specifications is guaranteed for a period of 12 months from the date of delivery, subject to appropriate storage. Appropriate storage refers to a warehouse, protecting the produt from outside weather conditions, such as direct sun light exposure, rain, swings in ambience temperature outside the interval of 17°C to 25°C and respecting the Stacking tests conditions, as referred above.

Quality information:

Deviations in the product specifications in this data sheet of 0,025% or less (i.e. 25 items per 100,000 pcs) are considered acceptable in the industry and therefore cannot be constructed as a defect. Also, please refer to the General Sales and Delivery conditions in force at the time of delivery.

Specifications are subject to change without notice.

Lastest revision: 09-01-2024